Boasting a stylish and contemporary design, the Prisma Keypad is an elegant solution for control of the Integriti system. Featuring a full-colour LCD display and intuitive navigation keys, end-users will delight in using this interface.

Just some of the functions supported include monitoring and acknowledging alarms and events, arming/disarming, unlocking/locking doors and isolating zones. Eight status LEDs can be used to display the armed/disarmed state of areas or for other intruder/access control/automation purposes. An in-built temperature sensor displays the local temperature and can also be integrated into the system for building automation control.

The "SI" version conveniently houses an in-built Inner Range SIFER card reader which can be used for general access control or for high-security "Card + PIN" authentication.

Features

- Contemporary slimline surface mount design
- Full-colour LCD backlit screen
- · Large easy to read text
- Icon and scroll wheel navigation system
- Function keys for quick item selection
- · Tamper monitored
- · Light sensitive auto-dimming LCD backlight
- · Variable colour RGB keypad backlight
- · Local temperature display
- 8 LED indicators for Area status display
- Instant help text available anytime, at the press of a key
- Programmable panic key and duress option


Additional Feature for SIFER model (SI Version)

- Inbuilt multi-format SIFER reader
- Support for all SIFER credentials
- Support for 13.56Mhz cards(CSN Only)
- · Card access control
- · Card & PIN access control
- · Card login
- Card & PIN login



Prisma is also available with a SIFER reader built in.

Connectivity



Specifications

Physical

Beeper/Speaker:	1	
LED Indicators:	8	
System Outputs		
Keypad Backlight:	Variable-colour RGB, Auto-dimmable	
LCD Backlight:	White backlit, Auto-dimmable	
LCD Screen:	320 x 240 (QVGA) colour LCD	
User Interface		
LED Indicators:	Array of 8, Auto-dimmable bi-colour LED	
Speaker:	8-bit digital sound	
Connections		
Operational Current:	Auto current limiting typically less than 100mA @12V	
Input Voltage:	11V – 14V DC	
Electrical		
Installation Environment:	0° - 50°C @ 15% to 85% relative humidity (non-condensing)	
Housing Dimensions:	162 (H) x 88(W) x 15(D) (mm)	

Ordering Options



996000

Integriti Prisma Keypad – White

996000SI

Integriti Prisma Keypad – White with built in multi-format SIFER reader



999059P

Security shroud to suit Prisma Terminal - White



